Evaluation of *Ulva reticulata* for the bioremediation of nutrients from Kelung River, Penang, Malaysia

Khodami Sh.^{1,3*}; Surif M.²; Wan Maznah W. O.^{2, 3}; Attaran Fariman G.⁴; Bahreinie P.⁵

Received: May 2023

Accepted: July 2023

Abstract

Urban, agriculture, aquaculture and industrial wastewater are rich in nitrogen and phosphorus, and it is necessary to reduce the concentrations of these nutrients in the effluent before wastewater can be discharged into the environment. This study examined the use of *Ulva reticulata* to remove nutrients from water that collected from Kelung River in the Bayan Lepas Free Industrial Zone, Penang, Malaysia. *Ulva reticulata* was exposed to water, and its nutrient uptake was measured at different times. The maximum ammonium and phosphate uptake rates occurred during the first hour of exposure ($V_{300\mu M}^{0-1}h = 32$ and $V_{50\mu M}^{0-1}h = 4 \mu mol g^{-1}$ fw h⁻¹, respectively). *U. reticulata* had removed 92.4% of the ammonium and 90% of the phosphate from water by 24 and 48 h, respectively. The growth rate of *U. reticulata* ranged from 3.24 to 4.0% day-1. Our results revealed that *U. reticulata* is an effective biofilter for ammonium and phosphate and will grow quickly in water that contaminated with nitrogen and phosphorus.

Keywords: Nutrient removal, Ulva reticulata, Bioremediation, Uptake rate

¹⁻ Iranian Fisheries Science Research (IFSR), P. O. Box: 14155-6116, Tehran, Iran

²⁻ Centre for Marine and Coastal Studies (CEMACS), Universiti Sains Malaysia, 11800 Penang, Malaysia

³⁻ School of Biological Sciences, Universiti Sains Malaysia, 11800 Penang, Malaysia

⁴⁻ Chabahar Maritime University, Chabahar, Iran

⁵⁻College of Science, Slippery Rock University, PA, 16057, United States

^{*}Corresponding autor's Email: shkhodami@yahoo.com

Introduction

Among the methods available for treating wastewater effluents, plants are a potential candidate for nutrient removal (Ansari et al., 2014; Fan et al., 2019; Kambey et al., 2020; Nguyen et al., 2022). Aquatic plants have been used in constructed wetlands for nutrient removal from domestic sewage and in agriculture wastewater treatment (Zhang et al., 2014; Jabłońska et al., 2021). The application of artificial wetlands has also been extended to treat other types of wastewater, such as industrial wastewater (Chen et al., 2006; Maine et al., 2006). Macroalgae are widely used in integrated aquaculture systems (Cohen and Neori, 1991; Chung et al., 2002; Neori et al., 2004; Marinho-Soriano et al., 2009; Al-Hafedh et al., 2012; Azman et al., 2014; Biswas et al., 2020; Kang et al., 2021). The excess nutrients from the uneaten food and feces of fish and shrimp are taken up by seaweed. The use of integrated systems balances nutrients and also produces aquatic animals and seaweed (Wu et al., 2015). Thus, it is an efficient and economically beneficial method that contributes to sustainable aquaculture (Mao et al., 2009). Among the different types of seaweed tested, the macroalgae of the Ulva genera have shown high nutrient-removal capabilities. Ulva have flat sheet morphotypes, which are associated with high nitrogen contents and growth rates. Such characteristics these macroalgae make excellent candidates for remediation (Cohen and Neori, 1991; Sode et al., 2013; Zhang et al., 2023).

Industrial activity, urbanization and agriculture have led to the increased production of wastewater and the release of different pollutants into aquatic systems (Abdolali et al., 2014; Azman et al., 2014; Garg et al., 2022). The effluent from wastewater includes nutrients that have been identified as the main causes of eutrophication in natural waters (Rasoul-Amini et al., 2014). Penang, in the northwest peninsula of Malaysia, has faced rapid development in both urban and industrial areas over the past 30 years. The area is industrialized and urbanized, and it is a well-known shipping route and a center of aquaculture and tourism (Sakari et al., 2008). Because these activities can cause environmental negative impacts, sustainable industrial development has been strongly emphasized (Wurts, 2000; Neori et al., 2004). The Free Industrial Zone (FIZ) in Bayan Lepas was established in southeastern Penang Island in 1972. The FIZ houses manufacturers of electronics, fabricated metal products, machinery and precision tools. Wastewater produced by the electronics industry often consists of high organic nitrogen (Chen et al., 2003a, b). Ammonium is the inorganic form of nitrogen found in industrial wastewater (Maine et al., 2006; Huang et al., 2018), and it can also arise from the decomposition of organic nitrogen (Zheng and Li, 1998). High nitrogen and phosphorus contents have been reported In metallurgic wastewater (Maine et al., 2006; Ji et al., 2022). The results obtained from a water assessment of the Bayan Lepas FIZ showed that among the nutrients analyzed, the ammonium and phosphate concentrations were very high in the factory area. Therefore, the concentrations of ammonium and phosphate in the effluent should be reduced before this wastewater can be discharged off the coast of Penang.

There is a lack of information regarding the use of seaweed for the removal of nutrients from wastewater in Malaysia. As *U. reticulata* is a local seaweed in Penang, it was assessed for its ability to act as a bioremediation agent for nutrient removal. The bioremediation potential of *U. reticulata* was investigated by determining the uptake rates of NH_4^+ , NO_3^- and PO_4^{3-} from contaminated water and by studying the specific growth rate of *U. reticulata* in wastewater.

Materials and methods

Ulva reticulata cultivation

U. reticulata was collected at the shore of Penang Island (5° 21' N, 100° 20' E) during low tide. The collected samples were then placed in a cool box and transported to the Centre for Marine and Coastal Studies (CEMACS), Universiti Sains Malaysia. To obtain uniform and readily available samples, U. reticulata was cultured at the CEMACS, which is located far from sites of industrial activity. Upon arrival at the CEMACS, the samples were washed with seawater until the seaweed was free from sand and organisms. The epiphytic washed samples were cultured in seawater for several months in 5 m (L) \times 2 m (W) \times 1 m (H) fiberglass tanks that were covered with one layer of black netting. After the cultivation period, the washed Ulva were then transported to a laboratory for further experimentation. In the laboratory, several 1 m (L)×0.60 m $(W) \times 0.45 \text{ m}$ (H) aguaria were filled with 30% artificial seawater. The seawater in laboratory was prepared the bv dissolving tap water with nutrient-free artificial salt (France). Prior to the nutrient uptake experiments, different light intensities (4, 10, 20 µmol photons m⁻² s⁻¹) were selected on the basis of preliminary experiments. Maintains of U. reticulata under a light intensity more than 4 µmol photons m⁻² s⁻¹ was caused to color changes of U. reticulata. Then, U. reticulata were maintained in aerated aquaria under a light intensity of 4 µmol photons m⁻² s⁻¹ and a 12-h light/dark photoperiod and acclimatized for five days. These Ulva cultures were used for subsequent experiments.

Wastewater sampling

Effluents from the Bayan Lepas FIZ are discharged into several drainage canals and the Keluang River, where they are finally released into the open sea across from Jerjak Island (Fig. 1); the Keluang River is the largest of the canals in the Bayan Lepas FIZ. To determine the uptake rates of the nutrients NH₄⁺, NO₃⁻ and PO_4^{3-} by U. reticulata, water was collected at the end of the Keluang River (in the factory region) during low tide. The water samples were transferred into a 10-L plastic jerry can at -4°C before transport to the laboratory. During sample collection, physicochemical parameters such as temperature, pH, dissolved oxygen and salinity were measured in situ using a multi-parameter probe, model YSI Pro Plus.



Figure 1: Map of the Peninsular Malaysia (a), Penang state (b), and Bayan Lepas FIZ (c).

Nutrient removal

The water was filtered through glass wool to remove dye and dregs. Preliminary experiments showed that the salinity ranged from 0 to 30% in industrial wastewater from the shore of Penang Island. Additionally, more than 90% of the water ammonium and phosphate was removed by *U. reticulata* after 48 and 72 h, respectively; however, nitrate was not removed during the experiment. Hence, the ammonium and phosphate removal and uptake rate experiments were performed at different salinities (0, 10, 20 and 30%) after 48 and 72 h, respectively. Artificial salt was added to wastewater in 500-mL conical flasks. Two grams of fresh U. reticulata was added to the experimental flasks. The ammonium and nitrate uptake rates were measured after 1, 3, 6, 12, 24 and 48 h, and the phosphate uptake rate was determined after 1, 12, 24, 48 and 72 h. The U. reticulata in the experimental flasks were exposed to a light intensity of 40 µmol photon m⁻² s⁻¹ under a 12-h light/dark photoperiod. Nutrient concentrations were measured using a spectrophotometer (Hach DR/ 2800) for fresh water, wastewater (Adams, 1991; APHA, 2005) and seawater (Grasshoff et al., 2009) samples. The uptake rate and the removal of ammonium, nitrate and phosphate were calculated as follows:

 $Uptake = \frac{(C_i - C_t) \times v}{m \times t}$

Where, uptake is (μ mol g⁻¹ fw h⁻¹), C_i and C_t are the concentrations (μ mol L⁻¹) at the beginning and end of the uptake, respectively, ν is the volume (L), *m* is the fresh weight of *Ulva* (g), and *t* is the time interval.

The removal of nutrients was calculated using the following formula:

Removal of nutrient (%) = $\frac{(C_0 - C_e)}{C_0} \times 100$

Where, C_0 is the initial nutrient concentration, and C_e is the residual nutrient concentration.

Results

The *U. reticulata* ammonium uptake rates in wastewater at different salinities (0, 10, 20, and 30%) over 48 hours are shown in Figure 2. The ammonium uptake rate increased rapidly during the first hour and then more gradually until 48 hours for all of the salinities tested.



Figure 2: *Ulva reticulata* ammonium uptake rates in wastewater with different salinities (0, 10, 20, and 30%) measured at 1, 3, 6, 12, 24 and 48 h (n=5).

Figure 3 presents the removal of ammonium (%) from wastewater by U. reticulata at different salinities (0, 10, 20, or 30%) over 48 hours. Ammonium removal increased from 1 to 48 hours but was much higher in the first 6 hours. The ammonium removal rates at different salinities showed similar fluctuations. but the highest value was attained at a salinity of 30%. The ammonium uptake increased as salinity increased. Evaluation of the ammonium removal by U. reticulata from wastewater at different salinities revealed that the

maximum removal occurred after 1 hour of exposure. The rate of ammonium removal (%) was significantly different between 1 and 24 h (one-way ANOVA, p<0.05), and approximately 90% of the ammonium was removed by 24 h at all salinities tested. After 24 h, the removal percentages were not significantly different (p>0.05).

Our results showed that there was no nitrate uptake by *U. reticulata* from the medium containing 300 μ M NH⁴⁺, 50 μ M PO₄³⁻ and 15 μ M NO₃⁻ over the course of the experiment (48 h).



Figure 3: Ammonium removal (%) from wastewater by *Ulva reticulata* at different salinities (0, 10, 20, and 30%) over 48 hours (n=5).

Figure 3 shows the U. reticulata phosphate uptake rate from wastewater at different salinities (0, 10, 20, and 30%) over 72 hours. The phosphate uptake rate decreased drastically from 1 to 24 h and then further decreased until 72 h. The phosphate uptake rate trends were nearly identical under different salinities. The highest phosphate uptake rate for each salinity (30, 20, 10 and 0%)was observed after 1 hour with values of 4.05±0.01, 3.1±0.02, 2.81± 0.02 and $2.54\pm0.03 \ \mu mol g^{-1} fw h^{-1}$, respectively. uptake rate increased with The increasing salinity from 0 to 30%. The phosphate uptake rate at 30% salinity initial with wastewater nutrient concentrations of 300 µM NH4⁺, 50 µM PO_4^{3-} and 15 µM NO_3^{-} was 4.05±0.01 µmol g⁻¹ fw h⁻¹. The percentage of phosphate removal by U. reticulata from wastewater at different salinities (0, 10, 20, or 30%) over 72 h is shown in Figure 4. The percentage of phosphate removal increased gradually from approximately 20% in the first hours to 90% after 48 h, and then the removal slowed from 48 to

72 h. In this study, wastewater with different salinities and an initial phosphate concentration of 50 μM exhibited an approximately 90% reduction in the level of phosphate after 48 h, and the phosphate removal percentages at all salinities tested were Phosphate similar. removal was significantly different (one-way ANOVA, p < 0.05) at different salinities after 1 hour; however, this difference was not significant (p>0.05) at different salinities after 48 h.

Discussion

The water was collected at 26°C and had 0% salinity, 2 mg L⁻¹ dissolved oxygen and a pH of 7.10. The ammonium, nitrate and phosphate concentrations were 300, 15 and 50 μ M, respectively. The ammonium concentration was high, whereas the dissolved oxygen level was very low. Sode *et al.* (2013) stated that ammonium is the dominant form of nitrogen in urban, aquacultural and agricultural wastewaters.



Figure 4: *Ulva reticulata* phosphate uptake rates from wastewater at different salinities (0, 10, 20, and 30%) measured at 1, 12, 24, 48 and 72 h (n=5).

Most macroalgae can take up nutrients over their surface area. Ulva has a foliated morphology and is able to take up nutrients to support its growth (Sode et al., 2013). Therefore, the high ammonium and phosphate concentrations of the Bayan Lepas FIZ wastewater were suitable for the growth of U. reticulate. Our results showed that the maximum ammonium uptake occurred in the first hour (31.97±1.84, 24.42±2.09, 19.01±2.16 and 5.47±1.44 µmol g⁻¹ fw h⁻¹ in 30, 20, 10 and 0% salinities, respectively). Similar results were observed by Luo et al. (2012), who reported that the maximum nutrient uptake rate occurred during the first hour of exposure. The ammonium uptake rates of Ulva linza and Ulva prolifera decreased over time, and their maximum uptake rates occurred within the first 30 minutes of exposure (Luo et al., 2012). The results obtained by comparing the ammonium uptake rates indicated that there was a significant difference (p < 0.05) before 24 hours; however, no significant difference was observed after 24 hours (one-way ANOVA). Moreover, the results showed that the uptake was significantly different between different salinities (one-way ANOVA, p<0.05). Nutrient uptake rates can be affected by various factors and should therefore be compared with caution. Our results showed that the ammonium uptake rate of U. reticulata in industrial wastewater containing initial concentrations of 300 μ M NH₄⁺, 50 μ M PO₄³⁻ and 15 μ M NO₃⁻ was 31.97 µmol g⁻¹ fw h⁻¹ (5.33 µmol g⁻¹ ¹ dw min⁻¹). Ammonium uptake rates at an initial concentration of 150 µM NH4⁺ were reported for Gracilaria textorii Harriot (0.28 µmoles g⁻¹ dw min⁻¹), Ulva pertusa Kjellman (1.91 µmoles g⁻¹ dw min⁻¹) and Porphyra tenera Kjellman $(3.44 \,\mu\text{moles g}^{-1} \,\text{dw min}^{-1})$ (Chung et al., 2002). In addition, the ammonium uptake rates at an initial concentration of 2 µM NH4⁺ were reported in Xiphophora 83eucosti (0.3 µmoles g⁻¹ dw h⁻¹) and Stichosiphonia arbuscula (2.4 µmoles g ¹ dw h^{-1}) (Phillips and Hurd, 2004). Consequently, a comparison of the ammonium uptake rates of other macroalgae with our results indicates that U. reticulata is a good candidate for

ammonium uptake in industrial wastewater.

In this study, Ulva was maintained at a salinity of 30%; when the salinity was changed from 30% to 20, 10 or 0%, the ammonium removal efficiency decreased. The relatively low Ulva uptake rates at salinities less than 30% may be due to the stress endured by Ulva upon salinity change, and the ammonium uptake rate and removal percentage after 1 hour were significantly different among salinities (p < 0.05). However, after 24 hours, these differences disappeared (p>0.05). When exposed to changes in salinity, most intertidal algae use a complex set of physiological biochemical and mechanisms to acclimate to fluctuating salinities in their habitats (Lobban, 1994). One typical tolerance mechanism in marine algae is the maintenance of constant cell turgor pressure with the use of changing osmotic potentials (Kirst, 1990). Therefore, it appears that U. reticulata uses a tolerance mechanism, given that the ammonium removal was nearly identical at all salinities after 24 hours.

The biofiltration capacity of NH_4^+ by *U. reticulata* in this study was 60, 84.6, 92.8 and 100% within 3, 6, 24 and 48 h, respectively. Cohen and Neori (1991) stated that various studies have reported nitrogen removal efficiencies in the range of 10 to 90% in polyculture systems. Ammonium removal by *Gracilaria caudata* was 59.5% within 4 h (Marinho-Soriano *et al.*, 2009), while *Gracilaria lemaneiformis* removed 60% within 8 days (Zhou *et al.*, 2006). *Ulva*

84*eucost* removed 45% and *Gracilaria edulis* removed 70% after 14 days (Azman *et al.*, 2014), and *Ulva* 84*eucost* removed 40-90% depending on the NH_{4^+} supply (Cohen and Neori, 1991).

The nitrate concentration in the experimental flasks also increased within 48 h. The ammonium concentration was 20-fold higher than the nitrate concentration. Nitrogen and phosphorus uptake depends on the media composition and environmental parameters, such as the initial nutrient concentrations, the ratio of nitrogen to phosphorus and light intensity (Aslan and Kapdan, 2006). Ammonium uptake rates with an initial NH4⁺ concentration of 150 µM were reported in Gracilaria verrucosa Papenfuss and Hypnea charoides Lamouroux (0.48 µmoles g⁻¹ dw min⁻¹) and *Porphyra serriata* Kjellman (2.89 µmoles g⁻¹ dw min⁻¹) (Chung et al.. 2002), whereas ammonium uptake rates with an initial NH_4^+ concentration of 2 μM were recorded in Apophlaea lyallii (0.6 µmoles g⁻¹ dw h⁻¹) and Stichosiphonia arbuscula (2.4 µmoles g⁻¹ dw h⁻¹) (Phillips and Hurd, 2004). In addition, Harrison and Hurd (2001) stated that when algae take up nitrate, it can be stored in the cytoplasm or a vacuole or it can be enzymatically reduced to nitrite (and subsequently to ammonium). Similarly, urea can be stored in the cytoplasm or a vacuole or consumed via the enzyme urease, thus reducing it to ammonium. Ammonium is assimilated or formed from nitrate or urea and is subsequently converted to an amino acid. Therefore, higher ammonium

uptake may be related to the lower energy required to assimilate NH_4^+ , as NO_3^- needs to be reduced to NH_4^+ by the enzyme nitrate reductase before assimilation can occur (Abreu *et al.*, 2011; Cai *et al.*, 2013).

The maximum and minimum rates of phosphate uptake by Ulva pertusa with an initial concentration of 8 µM PO₄³⁻ were reported to be 0.157 μ mol g⁻¹ dw h⁻ ¹ and 0.04 µmol g⁻¹ dw h⁻¹ at salinities of 25 and 15%, respectively (Choi et al., 2010). The highest phosphate uptake rates with an initial PO₄³⁻ concentration of 30 µM were reported in Porphyra 85eucosticte (16 μ mol g⁻¹ dw h⁻¹) and Porphyra rosengurttii (6 µmol g⁻¹ dw h⁻ ¹). The phosphate uptake rates of Porphyra 85eucosticte, Porphyra rosengurttii, Porphyra suborbiculata and Porphyra purpurea in a medium containing 30 µM NO₃⁻ and 3 µM PO₄³⁻ were higher than in a medium with 3 µM NO_3^- and 0.5 $\mu M PO_4^{3-}$; therefore, an increased initial phosphate concentration increased the uptake rate (Pedersen et al., 2004). Comparison of the U. reticulata phosphate uptake rate in this study with those of other macroalgae reported elsewhere should undertaken with caution. be The phosphate uptake rate depends on the initial nutrient concentrations in the medium, the duration of exposure, and the previous nutritional history of the algae; directly comparing these values can be misleading (Chopin et al., 1990). In addition, if researchers using fresh or dry seaweed do not report the ratio between fresh and dry macroalgae, a comparison of their results is not

feasible. However, the rate of phosphate uptake by *U. reticulata* was close to that of *U. pertusa*, as reported by Choi and Lee (2012).

A comparison between the phosphate and ammonium uptake rates showed similar trends and removal efficiencies at different salinities. Nevertheless, the ammonium uptake rate was higher than the phosphate uptake rate. The average N:P ratio for seaweeds is 30N:1P, ranging from 10:1 to 80:1 (Atkinson and Smith, 1983). These ratios indicate that seaweed requires nitrogen more than phosphorus, which explains the lower phosphate uptake rate compared to ammonium uptake. A comparison of ammonium removal with phosphate removal (Figs. 3 and 5) indicates that approximately 80% of the phosphate was removed by U. reticulata after 48 h. The rate of phosphate uptake was less than that of ammonium, and U. also required a longer reticulata exposure time to remove phosphate. The PO_4^{3-} biofiltration capacity of U. reticulata was 40, 70, 94 and 100% after 12, 24, 48 and 72 h, respectively (Fig. 5). A study on the PO₄³⁻ biofiltration capacity of Gracilaria caudate reported 12.3% phosphate removal from shrimpfarm wastewater (Marinho-Soriano et al., 2009), whereas Gracilaria chilensis removed 27% of the phosphate from salmon-farm effluents (Troell et al., 1997).

Our results revealed that U. reticulata removed ammonium (92.4%)and (90%) from wastewater phosphate within 24 and 48 h, respectively. reticulata Therefore. U_{\cdot} can be considered an effective biofilter for ammonium and phosphate in industrial wastewater.



Time (hour)

Figure 5: Phosphate removal (%) from wastewater by *Ulva reticulata* at different salinities (0, 10, 20, 30%) over 48 hours (n=5).

In summary, Kelung River in the Bayan Lepas FIZ exhibited high concentrations of ammonium and phosphate, which were suitable as nutrient resources for the growth of U. reticulata. This various organism showed nutrient uptake rates and preferred ammonium to nitrate; this organism also exhibited a broad salinity tolerance. These results reveal that U. reticulata has the potential to reduce ammonium and phosphate loading within 48 and 72 h, respectively, at different salinities (0, 10, 20, and 30%). These highly efficient uptake rates at different salinities, demonstrate that U. reticulata can remove high levels of ammonium and phosphate in seawater as well as contaminated water.

Acknowledgments

The authors are thankful to the Department of Fisheries Malaysia and Universiti Sains Malaysia for supporting this work. This research was supported by research grant 304/PJJAUH/650529/L119.

References

- Abreu, M.H., Pereira, R., Buschmann, A., Sousa-Pinto, I. and Yarish, C., 2011. Nitrogen uptake responses of Gracilaria vermiculophylla(Ohmi) Papenfuss under combined and single addition of nitrate and ammonium. *Journal of Experimental Marine Biology and Ecology*, 407, 190-199. DOI:10.1111/j.1529-17.2011.01004.x
- Adams, V., 1991. Water and wastewater examination manual, The united states of America, Lewis. DOI:10.1016/j.scitotenv.2021.150585
- Al-Hafedh, Y.S., Alam, A., Buschmann, A.H. and Fitzsimmons, K.M., 2012. Experiments on an integrated (seaweeds aquaculture system and marine fish) on the Red Sea coast of Saudi Arabia: efficiency comparison of two local seaweed species for nutrient biofiltration and production. Review Aquaculture, 4. 21-31. DOI:10.1111/j.1753-31.2012.01058.x
- Ansari, A.A., Gill, S.S., Khan, F.A. and Naeem, M., 2014. Phytoremediation systems for the recovery of nutrients from eutrophic waters. Eutrophication: Causes, Consequences and Control.

Springe, 2, 239-248. DOI:10.1007/978-94-007-7814-6_17

- APHA, 2005. Standard methods for the examination of water and wastewater, American Public Health Association Washington, DC. American Public Health Association.
- Aslan, S. and Kapdan, I.K., 2006. Batch kinetics of nitrogen and phosphorus removal from synthetic wastewater by algae. *Ecological Engineering*, 28, 64-70. DOI:10.1016/j.ecoleng.2006.04.003
- Atkinson, M. and Smith, S., 1983. C: N: P ratios of benthic marine plants1. *Limnology and Oceanography*, 28, 568-574. DOI:10.4319/lo.1983.28.3.0568
- Azman, S., Mohd Said, M. I., Ahmad, F. and Mohamad, M., 2014. Biofiltration potential of macroalgae for ammonium removal in outdoor tank shrimp wastewater recirculation system. *Biomass. Bioenerg.*, 66, 103-109.
- Biswas, G., Kumar P., Ghoshal, T., Kailasam, M., DE, D., Bera, A., Mandal, B., Sukumaran, K. and Viijan, K., 2020. Integrated multitrophic aquaculture (IMTA) outperforms conventional polyculture with respect to environmental remediation, productivity and economic return in brackishwater ponds. *Aquaculture*, 516, 734626. DOI:10.1016/j.aquaculture.2019.734626
- Cai, T., Park, S.Y. and Li, Y., 2013. Nutrient recovery from wastewater streams by microalgae: status and prospects. *Renewable and Sustainable Energy Reviews*, 19, 360-369. DOI:10.1016/j.rser.2012.11.030
- Chen, T., Ni, C. and Chen, J., 2003a. Nitrification–denitrification of optoelectronic industrial wastewater by anoxic/aerobic process. *J. Environ. Sci. Heal A*, 38, 2157-2167. DOI:10.1081/ESE-120024449

- Chen, T., Ni, C., Chen, J. and Lin, J., 2003b. High-strength nitrogen removal of opto-electronic industrial wastewater in membrane bioreactor- a pilot study. *Water. Sci .Technol.*, 48, 191-198. DOI:10.2166/wst.2003.0052
- Chen, T., Kao, C., Yeh, T., Chien, H. and Chao, A., 2006. Application of a constructed wetland for industrial wastewater treatment: A pilot-scale study. *Chemosphere*, 64, 497-502. DOI:10.1016/j.chemosphere.2005.10.01 6
- Choi, T.S., Kang, E.J., Kim, J.h. and Kim,
 K.Y., 2010. Effect of salinity on growth and nutrient uptake of *Ulva pertusa* (Chlorophyta) from an eelgrass bed. *Algae*, 25, 17-26. DOI:10.4490/algae.2010.25.1.017
- Choi, J.M. and Lee, C.W., 2012. Influence of elevated phosphorus levels in nutrient solution on micronutrient uptake and deficiency symptom deficiency symptom develoved in strawberry culture with frrtigaton system. *Journal of Plant Nutrition*, 35(9), 1349-1358. DOI:10.1080/01904167.2012.684130
- Chopin, T., Hourmant, A., Floc'h, J.-Y. and Penot, M. 1990. Seasonal variations of growth in the red alga *Chondrus crispus* on the Atlantic French coasts. II. Relations with phosphorus concentration in seawater and internal phosphorylated fractions. Canadian Journal of Botany, 68, 512-517. DOI:10.1139/b90-069
- Chung, I.K., Kang, Y.H., Yarish, C., Kraemer, G.P. and Lee, J.A., 2002. Application of seaweed cultivation to the bioremediation of nutrient-rich effluent. *Algae*, 17, 187-194. DOI:10.4490/algae.2002.17.3.187
- Cohen, I. and Neori, A., 1991. *Ulva lactuca* biofilters for marine fishpond effluents. I. Ammonia uptake kinetics and nitrogen

content. *Botanica Marina*, 34, 475-482. DOI:10.1515/botm.1991.34.6.475

- Fan, W., Zhao, R., Yao, Z., Xiao, C., Pan,
 Y., Chen, Y., Jiao, N. and Zhang, Y.,
 2019. Nutrient Removal from Chinese
 Coastal Waters by Large-Scale Seaweed
 Aquaculture Using Artificial Upwelling. *Water*, 11, 1754.
- Garg, S., Chowdhury, Z.Z., Faisal, A.N.M., Rumjit, N.P., Thomas, P., 2022. Impact of industrial wastewater on environment and human health. Advanced industrial wastewater Treatment and Reclamation of water: comparative Study of water pollution Index during pre-industrial, industrial Period and Prospect of wastewater Treatment for water resource 197-209. conservation, DOI:10.1007/978-3-030-83811-9 10
- Grasshoff, K., Kremling, K. and Ehrhardt, M., 2009. Methods of seawater analysis, John Wiley and Sons. DOI:10.1002/9783527613984
- Huang, J., Kankanamge, N.R., Chow, C., Welsh, D.T., Li, T. and Teasdale, P.R., 2018. Removing ammonium from water and wastewater using cost-effective adsorbents: A review. Journal of Environmental Sciences, 63, 174197. DOI:10.1016/j.jes.2017.09.009
- Jabłońska, E., Winkowska, M., Wiśniewska, M., Geurts, J., Zak, D., and Kotowski, W., 2021. Impact of vegetation harvesting on nutrient removal and plant biomass quality in wetland buffer zones. *Hydrobiologia*, 848, 3273-3289. DOI:10.1007/s10750-020-04256-4
- Ji, R., Liu, T.J., Kang, L.L., Wang, Y.T., Li, J.G., Wang, F.P., Yu, Q., Wang, X.M., Liu, H., Guo, H.W. and Xu, W.L., 2022. A review of metallurgical slag for efficient wastewater treatment:

Pretreatment,	perform	mance	and
mechanism.	Journal	of	Cleaner
Production,		380	.135076.
DOI:10.1016/j	.jclepro.20	22.135	076

- Kambey, C.S., Sondak, C.F. and Chung, I.K., 2020. Potential growth and nutrient removal of Kappaphycus alvarezii in a fish floating-net cage system in Sekotong Bay, Lombok, Indonesia. *Journal of the World Aquaculture Society*, 51(4), 944-959. DOI:10.1111/jwas.12734
- Kang, Y.H., Kim, S., Choi, S.K., Lee, H.J., Chung, I.K. and Park, S.R., 2021. A comparison of the bioremediation potential of five seaweed species in an integrated fish-seaweed aquaculture system: implication for a multi-species Seaweed culture. Reviews in 13(1), 353-364. Aquaculture, DOI:10.1111/raq.12478
- Kirst, G., 1990. Salinity tolerance of eukaryotic marine algae. Annu. Rev. Plant .Biol., 41, 21-53. DOI:10.1146/annurev.pp.41.060190.000 321
- Lobban, C.S., 1994. Seaweed ecology and physiology, Cambridge University Press. DOI:10.1017/CBO9780511626210
- Luo, M.B., Liu, F. and Xu, Z.L., 2012. Growth and nutrient uptake capacity of two co-occurring species, Ulva prolifera and Ulva linza. *Aquat. Bot.*, 100, 18-24. DOI:10.1016/j.aquabot.2012.03.001
- Maine, M., Sune, N., Hadad, H., Sánchez, G. and Bonetto, C., 2006. Nutrient and metal removal in a constructed wetland for wastewater treatment from a metallurgic industry. *Ecol. Eng.*, 26, 341-347.

DOI:10.1016/j.ecoleng.2005.12.004

Mao, Y., Yang, H., Zhou, Y., Ye, N. and Fang, J., 2009. Potential of the seaweed *Gracilaria lemaneiformis* for integrated multi-trophic aquaculture with scallop *Chlamys farreri* in North China. *Journal* of Applied Phycology, 21, 649-656. DOI:10.1007/s10811-009-9403-2

Marinho-Soriano, E., Panucci, R., Carneiro, M. and Pereira, D., 2009. Evaluation of *Gracilaria caudata* J. Agardh for bioremediation of nutrients from shrimp farming wastewater. *Bioresource Technology*, 100, 6192-6198.

DOI:10.1016/j.biortech.2009.06.08

Neori, A., Chopin, T., Troell, M., Buschmann, A.H., Kraemer, G.P., Halling, C., Shpigel, M. and Yarish, C., 2004. Integrated aquaculture: rationale, evolution and state of the art emphasizing seaweed biofiltration in modern mariculture. *Aquaculture*, 231, 361-391.

DOI:10.1016/j.aquaculture.2003.11.015

- Nguyen, Luong, N., Lisa Aditya, Hang, P.Vu, Abu Hasan Johir, Lucia Bennar,Peter Ralph, Ngoc B. Hoang, JakubZdarta, and Long D. Nghiem. 2022.Nutrient removal by algae-basedwastewater treatment. Current PollutionReports,8(4),369-383.DOI:10.101607/s40726-.022-003230-x
- Pedersen, A., Kraemer, G. and Yarish, C., 2004. The effects of temperature and nutrient concentrations on nitrate and phosphate uptake in different species of Porphyra from Long Island Sound (USA). Jounal of Experimental Marine Biology Ecology, 312, 235-252. DOI:10.1016/j.jembe.2004.07.004
- Phillips, J.C. and Hurd, C.L., 2004. Kinetics of nitrate, ammonium, and urea uptake by four intertidal seaweeds from Newzland. *Journal of Phycology*, 40, 534-545.

DOI:10.1111/j.15298817.2004.03114.x

Rasoul-Amini, S., Montazeri-Najafabady, N., Shaker, S., Safari, A., Kazemi, A., Mousavi, P., Mobasher, M.A. and Ghasemi, Y., 2014. Removal of nitrogen and phosphorus from wastewater using microalgae free cells in bath culture system. *Biocatalyst and Agriculture Biotechnology*, 3, 126-131. DOI:10.1016/j.bcab.2014.01.002

- Sakari, M., Zakaria, M.P., Lajis, N., Mohamed, C., Bahry, P. and Anita, S., 2008. Characterization, distribution. origins sources and of aliphatic hydrocarbons from surface sediment of Prai Strait, Penang, Malaysia: Α widespread anthropogenic input. Environ. Asia., 2, 1-14.
- Sode, S., Bruhn, A., Balsby, T. J., Larsen, M. M., Gotfredsen, A. and Rasmussen, M. B. 2013. Bioremediation of reject water from anaerobically digested waste water sludge with macroalgae (*Ulva lactuca*, Chlorophyta). *Bioresource Technology*, 146, 426-435. DOI:10.1016/j.biortech.2013.07.059
- Troell, M., Halling, C., Nilsson, A., Buschmann, A., Kautsky, N. and Kautsky, L., 1997. Integrated marine cultivation of *Gracilaria chilensis* (*Gracilariales*, Rhodophyta) and salmon cages for reduced environmental impact and increased economic output. *Aquaculture*, 156, 45-61. DOI:10.1016/S0044-8486(97)00080-3
- Wu, H., Huo, Y., Han, F., Liu, Y. and He, P., 2015. Bioremediation using *Gracilaria chouae* co-cultured with Sparus macrocephalus to manage the nitrogen and phosphorous balance in an IMTA system in Xiangshan Bay, China. *Marine Pollution Bulletin*, 91, 272-279. DOI:10.1016/j.marpolbul.2014.11.052
- Wurts, W.A., 2000. Sustainable aquaculture in the twenty-first century. *Rev.Fish* .*Sci.*, 8, 141-150. DOI:10.1080/1064126009112914

- Zhang, D., Jinadasa, K., Gersberg, R., Liu, Y., Ng, W. and Tan, S., 2014.
 Application of constructed wetlands for wastewater treatment in developing countries-A review of recent developments (2000-2013). *J. Environ. Manage.*, 141, 116-131.
 DOI:10.1016/j.jenvman.2014.03.015
- Zhang, L., Gao, G., Wei, B., Jin, M., and Xu, Y., 2023. Potential of green macroalgae (*Ulva*) in removing nutrients from saline aquaculture wastewater. *Marine Pollution Bulletin*, 186, 114385. DOI:10.1016/j.marpolbul.2023.
- Zheng, X. and Li, Y., 1998. Technology of phosphorus and nitrogen removal from wastewater. China Architectural Industry Press, Beijing, 4-11.
- Zhou, Y., Yang, H., Hu, H., Liu, Y., Mao,
 Y., Zhou, H., Xu, X. and Zhang, F.,
 2006. Bioremediation potential of the macroalga *Gracilaria lemaneiformis* (Rhodophyta) integrated into fed fish culture in coastal waters of north China. *Aquaculture*, 252, 264-276. DOI:10.1016/j.aquaculture.2005.07.02